

AQUA TROLL 100 DATA LOGGER

SKU: INS-AQT-100

Measure and record temperature and conductivity with the Aqua TROLL 100. See live readings in the Blueye App and export dive logs with insightful plots of the parameters.

Supplier: In-Situ



TECHNICAL SPECIFICATIONS

Physical details probe

Length	315 mm / 12.4 in
Diameter	18.3 mm / 0.72 in
Weight	188 g / 0.41 lb
Depth rating	340 m / 1,115 ft
Operating temperature	-5°C (23°F) to 50°C (122°F)
Material	Titanium body and sensors, Delrin® nose cone, and PVC conductivity cell
Supported parameters	Temperature Conductivity
Reading rate	New readings every second

Temperature sensor

Method	EPA Method 170.1
Accuracy & Resolution	Accuracy: $\pm 0.1^\circ\text{C}$. Resolution: 0.01°C or better
Units of measure	Celsius or Fahrenheit
Warranty	2 years. Up to 5-year (total) extended warranties available.

Conductivity sensor

Type	Balanced 4-electrode cell
Methods	EPA Method 120.1; Standard Methods 2510

Range	0 to 100,000 $\mu\text{S}/\text{cm}$
--------------	--------------------------------------

Accuracy	$\pm 0.5\%$ of reading + 1 $\mu\text{S}/\text{cm}$ when reading less than 80,000 $\mu\text{S}/\text{cm}$ $\pm 1.0\%$ of reading when reading above 80,000 $\mu\text{S}/\text{cm}$
-----------------	---

Resolution	0.1 $\mu\text{S}/\text{cm}$
-------------------	-----------------------------

Parameters supported	Actual conductivity Specific conductivity Salinity Total dissolved solids Resistivity Density (water salinity)
-----------------------------	---
